

<b>AMENDMENT OF SOLICITATION/MODIFICATION OF CONTRACT</b>			1. CONTRACT ID CODE N/A		PAGE 1 OF 8 PAGES		
2. AMENDMENT/MODIFICATION NO. 0004		3. EFFECTIVE DATE JUL. 19, 2002		4. REQUISITION/PURCHASE REQ. NO. N/A		5. PROJECT NO. (If applicable) SPEC. NO. 1266	
6. ISSUED BY CODE		7. ADMINISTERED BY (If other than Item 6) CODE					
DEPARTMENT OF THE ARMY U.S. ARMY ENGINEER DISTRICT, LOS ANGELES LOS ANGELES, CALIFORNIA 90053-2325				DISTRICT ENGINEER U.S. ARMY ENGINEER DISTRICT, LOS ANGELES 911 WILSHIRE BLVD LOS ANGELES, CALIFORNIA 90053-2325			

8. NAME AND ADDRESS OF CONTRACTOR (No., street, county, State and ZIP Code)		(✓)	9A. AMENDMENT OF SOLICITATION NO. DACA05-02-B-0002
		✗	9B. DATED (SEE ITEM 11) N/A
			10A. MODIFICATION OF CONTRACTS/ORDER NO. N/A
			10B. DATED (SEE ITEM 13) N/A
CODE		FACILITY CODE	

**11. THIS ITEM ONLY APPLIES TO AMENDMENTS OF SOLICITATIONS**

☒ The above numbered solicitation is amended as set forth in Item 14. The hour and date specified for receipt of Offers ☒ is extended, ☐ is not extended.

Offers must acknowledge receipt of this amendment prior to the hour and date specified in the solicitation or as amended, by one of the following methods:

(a) By completing Items 8 and 15, and returning 1 copies of the amendment; (b) By acknowledging receipt of this amendment on each copy of the offer submitted; or (c) By separate letter or telegram which includes a reference to the solicitation and amendment numbers. FAILURE OF YOUR ACKNOWLEDGMENT TO BE RECEIVED AT THE PLACE DESIGNATED FOR THE RECEIPT OF OFFERS PRIOR TO THE HOUR AND DATE SPECIFIED MAY RESULT IN REJECTION OF YOUR OFFER. If by virtue of this amendment you desire to change an offer already submitted, such change may be made by telegram or letter, provided each telegram or letter makes reference to the solicitation and this amendment, and is received prior to the opening hour and date specified.

12. ACCOUNTING AND APPROPRIATION DATA (If required)	
N/A	NOTE: ITEM 13 BELOW IS N/A.

**13. THIS ITEM APPLIES ONLY TO MODIFICATIONS OF CONTRACTS/ORDERS, IT MODIFIES THE CONTRACT/ORDER NO. AS DESCRIBED IN ITEM 14.**

(✓)	A. THIS CHANGE ORDER IS ISSUED PURSUANT TO: (Specify authority) THE CHANGES SET FORTH IN ITEM 14 ARE MADE IN THE CONTRACT ORDER NO. IN ITEM 10A. N/A
	B. THE ABOVE NUMBERED CONTRACT/ORDER IS MODIFIED TO REFLECT THE ADMINISTRATIVE CHANGES (such as changes in paying office, appropriation date, etc.) SET FORTH IN ITEM 14, PURSUANT TO THE AUTHORITY OF FAR 43.103(b).
	C. THIS SUPPLEMENTAL AGREEMENT IS ENTERED INTO PURSUANT TO AUTHORITY OF:
	D. OTHER (Specify type of modification and authority) N/A

**E. IMPORTANT:** Contractor ☐ is not, ☐ is required to sign this document and return\_\_\_\_\_ copies to the issuing office.

14. DESCRIPTION OF AMENDMENT/MODIFICATION (Organized by UCF section headings, including solicitation/contract subject matter where feasible.)	
557th DS Maintenance Shop Fort Irwin, CA	
<b>NOTE: Delete Specification Section 02555 (Roller Compacted Concrete Pavement) in its entirety.</b>	

**The Bid Opening has been changed to: July 30, 2002.**

2 Encl.

1. Revised Pages: Frontend Page(1,2, 8), 01505-10, 01505-11, 01505-12, 02821-7

2. Revised Drawings: C1.40, C1.41, S5.03, E2.11, E2.18, E2.19, E5.11

15A. NAME AND TITLE OF SIGNER (Type or print)		16A. NAME AND TITLE OF CONTRACTING OFFICER (Type or print)	
15B. CONTRACTOR/OFFEROR		16B. UNITED STATES OF AMERICA	
<div style="border-bottom: 1px solid black; width: 100%;"></div> (Signature of person authorized to sign)		BY <div style="border-bottom: 1px solid black; width: 100%;"></div> (Signature of Contracting Officer)	
15C. DATE SIGNED		16C. DATE SIGNED	

NSN 7540-01-152-8070  
PREVIOUS EDITION UNUSABLE
30-105-02
STANDARD FORM 30 (REV. 10-83)  
Prescribed by GSA  
FAR (48 CFR) 53.243
USAPPC V2.00

<b>SOLICITATION, OFFER, AND AWARD</b> <i>(Construction, Alteration, or Repair)</i>	1. SOLICITATION NO. DACA05-02-B-0002	2. TYPE OF SOLICITATION <input checked="checked" type="checkbox"/> SEALED BID (IFB) <input type="checkbox"/> NEGOTIATED (RFP)	3. DATE ISSUED 18-Jun-2002	PAGE OF PAGES 1 OF 186
<b>IMPORTANT - The "offer" section on the reverse must be fully completed by offeror.</b>				
4. CONTRACT NO.	5. REQUISITION/PURCHASE REQUEST NO. W62N6M-2122-5933		6. PROJECT NO.	
7. ISSUED BY DEPARTMENT OF THE ARMY CORPS OF ENGINEERS, SACRAMENTO 1325 J STREET SACRAMENTO CA 95814-2922  TEL: (916) 557-5238      FAX: (916) 557-7842	CODE DACA05	8. ADDRESS OFFER TO <i>(If Other Than Item 7)</i> DEPARTMENT OF THE ARMY CORPS OF ENGINEERS, LOS ANGELES ATTN: CONTRACTING DIVISION P.O. BOX 532711 LOS ANGELES, CA 90053-2325  TEL:      FAX:		
9. FOR INFORMATION CALL:	A. NAME MS. CHERYL GANNAWAY		B. TELEPHONE NO. <i>(Include area code)</i> <i>(NO COLLECT CALLS)</i> 916.557.6933	
<b>SOLICITATION</b>				
<b>NOTE: In sealed bid solicitations "offer" and "offeror" mean "bid" and "bidder".</b>				
10. THE GOVERNMENT REQUIRES PERFORMANCE OF THE WORK DESCRIBED IN THESE DOCUMENTS <i>(Title, identifying no., date):</i>  557th DS Maintenance Shop @ Fort Irwin, California Spec. No. 1266  Description: Construct a Direct Support (DS) Vehicle Maintenance Facility, consisting of hardstand parking of approximately 1,400,000 SF, Vehicle Maintenance Shop of approx. 59,000 SF, and elevator and a two-bay wash facility outside of the facility. Also, included is an approx. 900 SF Development Storage Facility. Supporting facilities shall include utilities; electrical services; fire protection and alarm systems; paving; sidewalks; curbs and gutters; parking; security fence and lighting; information systems; and site improvements.  ANY CONTRACT AWARDED UNDER THIS SOLICITATION WILL BE MADE PURSUANT TO PUBLIC LAW 100-656, SMALL BUSINESS COMPETITIVENESS DEMONSTRATION PROGRAM.  Estimated Cost Range: \$10,000,000.00 to \$25,000,000.00				
11. The Contractor shall begin performance within <u>10</u> calendar days and complete it within <u>365</u> calendar days after receiving <input type="checkbox"/> award, <input checked="checked" type="checkbox"/> notice to proceed. This performance period is <input checked="checked" type="checkbox"/> mandatory, <input type="checkbox"/> negotiable. <i>(See FAR 52.211-10 _____.)</i>				
12 A. THE CONTRACTOR MUST FURNISH ANY REQUIRED PERFORMANCE AND PAYMENT <i>(If "YES," indicate within how many calendar days after award in Item 12B.)</i> <input checked="checked" type="checkbox"/> YES <input type="checkbox"/> NO			12B. CALENDAR DAYS  10	
13. ADDITIONAL SOLICITATION REQUIREMENTS: A. Sealed offers in original and <u>0</u> copies to perform the work required are due at the place specified in Item 8 by <u>13:00:00</u> <i>(hour)</i> local time <u>7/30/02</u> <i>(date)</i> . If this is a sealed bid solicitation, offers must be publicly opened at that time. Sealed envelopes containing offers shall be marked to show the offeror's name and address, the solicitation number, and the date and time offers are due. B. An offer guarantee <input checked="checked" type="checkbox"/> is, <input type="checkbox"/> is not required. C. All offers are subject to the (1) work requirements, and (2) other provisions and clauses incorporated in the solicitation in full text or by reference. D. Offers providing less than <u>60</u> calendar days for Government acceptance after the date offers are due will not be considered and will be rejected.				

**SOLICITATION, OFFER, AND AWARD**

DACA05-02-B-0002

*(Construction, Alteration, or Repair)*

Page 2 of 186

**OFFER (Must be fully completed by offeror)**

14. NAME AND ADDRESS OF OFFEROR (Include ZIP Code)		15. TELEPHONE NO. (Include area code)
		16. REMITTANCE ADDRESS (Include only if different than Item 14)
CODE	FACILITY CODE	

17. The offeror agrees to perform the work required at the prices specified below in strict accordance with the terms of this solicitation, if this offer is accepted by the Government in writing within \_ calendar days after the date offers are due. (Insert any number equal to or greater than the minimum requirements stated in Item 13D. Failure to insert any number means the offeror accepts the minimum in Item 13D.)

AMOUNTS	SEE SCHEDULE OF PRICES
---------	------------------------

18. The offeror agrees to furnish any required performance and payment bonds.

**19. ACKNOWLEDGMENT OF AMENDMENTS***(The offeror acknowledges receipt of amendments to the solicitation -- give number and date of each)*

AMENDMENT NO.										
DATE										

20A. NAME AND TITLE OF PERSON AUTHORIZED TO SIGN  
OFFER (Type or print)

20B. SIGNATURE

20C. OFFER DATE

**AWARD (To be completed by Government)**

21. ITEMS ACCEPTED:

22. AMOUNT	23. ACCOUNTING AND APPROPRIATION DATA
------------	---------------------------------------

24. SUBMIT INVOICES TO ADDRESS SHOWN IN  
(4 copies unless otherwise specified)

**ITEM**

25. OTHER THAN FULL AND OPEN COMPETITION PURSUANT TO

☐ 10 U.S.C. 2304(c) ☐ 41 U.S.C. 253(c)

26. ADMINISTERED BY CODE

27. PAYMENT WILL BE MADE BY CODE

**CONTRACTING OFFICER WILL COMPLETE ITEM 28 OR 29 AS APPLICABLE**

☐ 28. NEGOTIATED AGREEMENT (Contractor is required to sign this document and return \_\_\_\_\_ copies to issuing office.) Contractor agrees to furnish and deliver all items or perform all work, requisitions identified on this form and any continuation sheets for the consideration stated in this contract. The rights and obligations of the parties to this contract shall be governed by (a) this contract award, (b) the solicitation, and (c) the clauses, representations, certifications, and specifications or incorporated by reference in or attached to this contract.

☐ 29. AWARD (Contractor is not required to sign this document.)

Your offer on this solicitation, is hereby accepted as to the items listed. This award consummates the contract, which consists of (a) the Government solicitation and your offer, and (b) this contract award. No further contractual document is necessary.

30A. NAME AND TITLE OF CONTRACTOR OR PERSON  
TO SIGN (Type or print)

31A. NAME OF CONTRACTING OFFICER (Type or print)

30B. SIGNATURE

30C. DATE

31B. UNITED STATES OF AMERICA  
BY

31C. AWARD DATE

52.0214-5001 DIRECTIONS FOR SUBMITTING BIDS (APR 2002)

Envelopes containing bids must be sealed, marked and addressed as follows:

MARK ENVELOPES:

Bid under IFB No. DACA05-02-B-0002  
***Bid Opening Date: JULY 30, 2002***

ADDRESS ENVELOPES TO:

Department of the Army  
U. S. Army Engineer District, Los Angeles  
ATTN: Contracting Division  
C/O: Ms. Lucia Carvajal  
P. O. Box 532711  
Los Angeles, CA 90053-2325

SPECIAL INSTRUCTIONS PERTAINING TO HAND-CARRIED BIDS:

Due to security precautions, all Corps of Engineers visitors/couriers are now required to check in at the Public Affairs Office (PAO), Suite 980, 911 Wilshire Blvd, Los Angeles, CA. Bidders are no longer permitted to hand-carry their bids directly to Contracting Division without an authorized escort. Bids may NOT be left unattended at the Public Affairs Office (PAO), Suite 980.

Bidders who desire to hand-deliver their bids prior to the scheduled bid opening time/date must notify the Contracting Division to arrange for receipt of their bid by Contracting Division personnel. Normally the contact will be the Contract Specialist designated above. In the event the Contract Specialist cannot be reached, please call the main Contracting Division telephone number, 213-452-3231 or the following alternative telephone numbers -3233, -3245, -3234, or -3235, in order to request assistance.

30 minutes prior to the scheduled bid opening time/date, the Bid Opening Officer will be in the Public Affairs Office (PAO) Suite 980, to accept bids. After visitor in-processing, all bidders will subsequently be escorted to Bid Opening Room, where the bids will be publicly opened and read.

In order to expedite visitor processing, bidders are encouraged to complete the information requested on the Notice of Visitor(s) Form (attached). The completed form can be faxed to the Contract Specialist at (213)452-4184 or 4187, prior to the date for receipt of bids. In addition, no more than 2 visitors per firm will be permitted within the building. No exceptions will be made. The offeror is responsible for compliance with the security requirements and shall ensure that any company representative, courier or delivery personnel are aware of these special procedures pertaining to hand carried bids.

(C) Contaminated soil:

This project is located in a traditional non-hazardous location, the surface is unused desert environment. In the event of an encounter with contamination during construction, the following specific guidance will apply:

(1) If visual evidence and/or detectable odor is encountered, construction work shall stop immediately and the Contractor shall notify the Post Environmental Branch, extension 3740. The Directorate of Public Works (DPW) Environmental Branch will immediately perform a preliminary site investigation to include samples and analysis. Then, based on findings, will initiate clean up procedures. After clean up procedures are completed, the area will be resampled and reanalyzed to certify that the area is clean of contamination and if clean, work would be allowed to continue. The DPW Environmental Branch will certify in writing that the area is clean and construction work may continue.

1.13 CONTRACTOR SAFETY PERSONNEL REQUIREMENTS (1985 JAN HQ USACE)

(A) On-site, safety coverage by contractors shall be required for the life of the contract.

(B) The Prime Contractor's Superintendent

The Prime Contractor **shall employ a full-time Safety Officer** that shall take an active role in enforcing the safety requirements by participation in safety conferences, hazard analysis, tool box meetings, walk-through inspections, correction of violations, etc., and including that of the subcontractor's work.

1.14 MONTHLY SAFETY INSPECTION

A monthly on-site inspection will be made by the insurance carriers of the prime and subcontractors. The Contractor's safety program will be reviewed and a meeting will be held with the Contracting Officer's Representative to discuss the job-site safety. A written report will be made by the Contractor stating the results of the inspection and the action taken.

1.15 WARRANTY PROBLEM PROCEDURE

Upon receipt of the written notice from the Contracting Officer as stated in paragraph WARRANTY OF CONSTRUCTION, subparagraph 5, the Contractor shall report to Building Number 384, BSI Work Order Branch, to pick up a copy of the work order describing the warranty problem. After the warranty item has been corrected the Contractor shall return the completed work order to Building Number 384 and indicate the corrective action taken.

1.16 AGGREGATE SOURCES

(A) Concrete aggregates may be produced from the approved sources listed below:

(1) Sources of fine aggregate. (List the sources in an appropriate manner.)

(2) Sources of coarse aggregate. (List the sources in an appropriate manner.)

(B) Concrete aggregates may be furnished from any of the above listed sources or at the option of the Contractor may be furnished from any other source designated by the Contractor and approved by the Contracting Officer, subject to the conditions hereinafter stated.

(C) After the award of the contract, the Contractor shall designate in writing, only one source or one combination of sources from which he proposes to furnish aggregates. If the Contractor proposes to furnish aggregates from a source or from sources not listed above, he may designate only a single source or a single combination of sources for aggregates. Samples for acceptance testing shall be provided as required by Section: of the Technical Specifications. If a source for coarse or fine aggregate so designated by the Contractor is not approved for use by the Contracting Officer, the Contractor may not submit for approval other sources but shall furnish the coarse or fine aggregate, as the case may be, from a listed source listed above at no additional cost to the Government.

(D) Listing of a concrete aggregate source is not to be construed as approval of all material from that source. The right is reserved to reject materials from certain localized areas, zones, strata, or channels, when such materials are unsuitable for concrete aggregate as determined by the Contracting Officer. Materials produced from a listed source shall meet all the requirements of the Technical Specifications of these specifications.

#### 1.17 COLOR SCHEME FOR CONTRACTOR FACILITIES

(A) All Contractor storage and operational facilities including temporary structures, signs and fencing, that remain at the site shall be compatible with the color scheme used on the project signs as directed by the Contracting Officer.

#### 1.18 AGGREGATE SOURCES

(A) Concrete aggregates can potentially be produced from the available on post sources listed below:

(1) Sources of fine aggregate.

a. Fine Aggregate Borrow Site No. 3 on Ft. Irwin\*

(2) Sources of coarse aggregate.

a. Coarse Aggregate Borrow Site No. 1 on Ft Irwin\*

*\*For locations and log descriptions of the "on-post" borrow sites refer to the contract drawings (sheets B6.007, B3.008-B3.010). At this time the Ft. Irwin DPW does not permit Fine Aggregate Borrow Site No. 2 as an aggregate source. In order to meet the specified requirements indicated in the section specifications, the aggregate sources shall require processing, crushing and washing before mixture proportioning can be done. It should be understood, that not all the material found in the aggregate source is adequate for use as aggregates. There will be some materials located in the borrow source that will not provide the desired results and will need to be wasted.*

(B) Concrete aggregates may be furnished from any of the above listed sources or at the option of the Contractor may be furnished from any other source approved by the Contracting Officer, subject to the conditions hereinafter stated. The Contractor shall provide tests that prove both the on and the off-post aggregate sources meet the requirements specified in Section: 02753.

(C) After the award of the contract, the Contractor shall designate in writing, only one source or one combination of sources from which he proposes to furnish aggregates. If the Contractor proposes to furnish aggregates from a source or from sources not listed above, he shall designate only a single source or a single combination of sources for aggregates. Samples for acceptance testing shall be provided as required by Section: 02753 of the Technical Specifications. If a source for coarse or fine aggregate not listed above is not approved for use by the Contracting Officer, the Contractor shall not submit for approval other sources but shall furnish the coarse or fine aggregate, as the case may be, from a source listed above at no additional cost to the Government.

(D) Listing of a concrete aggregate source shall not to be construed as approval of all material from that source. The right is reserved to reject materials from certain localized areas, zones, strata, or channels, when such materials are unsuitable for concrete aggregate as determined by the Contracting Officer. Materials produced from a listed source shall meet all the requirements of Section: 02753 of the Technical Specifications of these specifications.

(E) Explorations of On-Post Sources: The on-post aggregate sites have been explored by the Government to determine the character and extent of materials available. The locations of the exploration trenches and their corresponding logs are shown on the contract drawings. These data are the result of limited explorations and tests conducted by and for the Government, and are accurate to the extent of the scope of the investigations conducted. The Government shall not be responsible for any deduction, interpretation or conclusion drawn there from by the Contractor.

(F) Operations for On-Post Sources:

(1) Limits of Work Area: The limits of the area within which operations may be carried must be coordinated with the on post DPW. The depth to which the Contractor may operate shall be subject to approval, but shall be limited only by the extent of the existence of satisfactory material.

(2) Disposal of Waste Materials: All overburden removed, and all other waste material including materials designated unsuitable for use in the production of concrete aggregate shall be disposed of in approved disposal areas. All disposal areas shall be left in a neat and slightly condition, graded and sloped to drain properly to the satisfaction of the Contracting Officer. No separate payment will be made for the disposal of waste material but the cost thereof shall be included in the respective bid prices for the various parts of the concrete work in which the aggregates are used.

(3) Plan of Operations: Prior to beginning operations in the deposit, the Contractor shall submit a plan of operation in sufficient detail to indicate the following:

- (i) The proposed extent of the operation including depth.
- (ii) The method and schedule of overburden stripping operations.
- (iii) The proposed location of waste disposal areas.

The plan of operations in the deposit shall be subject to approval, but approval of the plan will not in any way relieve the Contractor of the responsibility to operate in the deposit in a safe and systematic manner.

PART 2 PRODUCTS (NOT USED)

PART 3 EXECUTION (NOT USED)

secured to the barbed wire at the two points and at every spiral turn of both coils as shown on the drawings.

### ~~3.11 GROUNDING~~

~~Fences crossed by overhead powerlines in excess of 600 volts shall be grounded as specified in Section 13100 LIGHTNING PROTECTION SYSTEM. Electrical equipment attached to the fence shall be grounded as specified in [Section 16370 ELECTRICAL DISTRIBUTION SYSTEM, AERIAL] [Section 16375 ELECTRICAL DISTRIBUTION SYSTEM, UNDERGROUND].] [Fences shall be grounded on each side of all gates, at each corner, at the closest approach to each building located within 50 feet of the fence, and where the fence alignment changes more than 15 degrees. Grounding locations shall not exceed 650 feet. Each gate panel shall be bonded with a flexible bond strap to its gate post. Fences crossed by powerlines of 600 volts or more shall be grounded at or near the point of crossing and at distances not exceeding 150 feet on each side of crossing. Ground conductor shall consist of No. 8 AWC solid copper wire. Grounding electrodes shall be 3/4 inch by 10 foot long copper clad steel rod. Electrodes shall be driven into the earth so that the top of the electrode is at least 6 inches below the grade. Where driving is impracticable, electrodes shall be buried a minimum of 12 inches deep and radially from the fence. The top of the electrode shall be not less than 2 feet or more than 8 feet from the fence. Ground conductor shall be clamped to the fence and electrodes with bronze grounding clamps to create electrical continuity between fence posts, fence fabric, and ground rods. After installation the total resistance of fence to ground shall not be greater than 25 ohms.~~

-- End of Section --